

Printed: 02/12/2004


CLMSPAMD

03810533

10

CLAIMS

1. Use of an organophosphonate having the general formula (I):



- 5 wherein

$\text{Z} = -\text{CHR}_1\text{PO}_3\text{R}_2$

$\text{R} = \text{H}, \text{CH}_3, \text{C}_2\text{H}_5 \text{ or } \text{M}$

$\text{R}' = \text{H}, \text{CH}_3, \text{CR}_3, \text{C}_6\text{H}_5, \text{ or } \text{SO}_3\text{H}_2$

$\text{M} = \text{alkali metal or ammonium ion}$

- 10 $n = 0 \text{ to } 10$

$m = 0 \text{ to } 10$

$a = 0 \text{ to } 10$

$b = 0 \text{ to } 10$

$c = 0 \text{ or } 1$

- 15 $x = 0 \text{ to } 10$

$y = 0 \text{ to } 10$

to inhibit white rust corrosion in water using systems.

2. Use as claimed in Claim 1, in which R and R' each = H , $n = 6$, m
 20 = 6, $c = 1$, $y = 0$ whereby the compound is
 bis(hexamethylene)triamine-pentakis (methylene phosphonic acid), as in
 formula (II):


BEST AVAILABLE COPY

Printed: 02/12/2004

CLMSPAMD

03810533

11



3. Use of a random copolymer of vinylidene diphosphonic acid and vinyl sulphonic acid in a molar ratio of between 1:1 and 1:500 to inhibit white corrosion in water using systems.
- 5
4. A compound as claimed in Claim 3, in which the molar ratio is 1:100 molar.
- 10
5. Use as claimed in Claim 3 or Claim 4, in which the molar ratio is 1:20 molar.
- 15
6. Use of a composition comprising a phosphonated oligomer of formula (I) as defined in Claim 1 or a random copolymer of vinylidene diphosphonic acid and vinyl sulphonic acid in a molar ratio of between 1:1 and 1:500, together with additives conventionally used in the water treatment industry to inhibit white rust corrosion in water using systems.
- 20
7. Use as claimed in Claim 6 in which the additives are selected from the group consisting of phosphonocarboxylic acids or salts and dispersants.
- 25
8. Use as claimed in Claim 7 in which the dispersant is a polyacrylate.
9. A composition as claimed in any one of Claims 6 to 8 in which the composition comprises a biocide.

BEST AVAILABLE COPY

Printed: 02/12/2004 ..

CLMSPAMD

03810533

12

10. Use as claimed in any one of Claims 6 to 9 in which the phosphonocarboxylic acid or salt is a phosphonated oligomer of maleic acid, of general formula (III):



wherein M is a cation such that the oligomer is soluble in water, and n is greater than 1.

10 11. Use as claimed in any one of Claims 6 to 9, in which the polyacrylate compound is a low molecular weight polymer having a molecular weight between 2000 to 5000.

15 12. A method for inhibiting corrosion in, or in connection with, a water-using system, said method consisting of the application or addition to said system of an effective amount of a phosphonated oligomer of formula (I) as defined in Claim 1 or a random copolymer of vinylidene diphosphonic acid and vinyl sulphonic acid in a molar ratio of between 1:1 and 1:500 or of a composition comprising a phosphonated oligomer of
20 formula (I) as defined in Claim 1 or a random copolymer of vinylidene diphosphonic acid and vinyl sulphonic acid in a molar ratio of between 1:1 and 1:500, together with additives conventionally used in the water treatment industry to inhibit white rust corrosion in water using systems..

25 13. A method as claimed in Claim 12 in which the method consists of the application to a metal prior to contact with water of an effective amount of the phosphonated oligomer or the random copolymer of vinylidene diphosphonic acid and vinyl sulphonic acid or of the composition.

30

BEST AVAILABLE COPY

Printed: 02/12/2004

CLMSPAMD

03810533

13

14. A method as claimed in Claim 12 or 13, in which the oligomer or copolymer is used in an effective amount of up to 1000 ppm.

5 15. A method as claimed in Claims 12 to Claim 14, in which the oligomer or copolymer is used in an effective amount of up to 250 ppm.

16. A method as claimed in any one of Claims 12 to 15 in which the oligomer or copolymer is used in an effective amount of up to 100 ppm.

10

BEST AVAILABLE COPY